

Chiral LLC

14030 Gannet Street - Suite C, Santa Fe Springs, CA 90670

Phone: (562) 921-0444 Fax: (562) 921-0034

Material Data Sheet

Material: *Wanthane WHT-6190*
Generic: *Linear Hydroxyl Polyurethane*

<i>Property</i>	<i>Data</i>	<i>Units</i>	<i>ASTM</i>
GENERAL			
Features	High Bonding Strength and Peel Strength Easy to Process by Extrusion Hot Melt Processes Easy to Dissolve in Usual Solvents		
Applications	Shoes Fire Hose Fabric Coating Urethane Glues		
Form	Pellets		
Processing Method	Extrusion		
PHYSICAL			
Melt Flowing Point	55 (131)	°C (°F)	
Viscosity (15% MEK, 23°C)	300~1500		
Glass Transition Temperature	180~200 (356-392)	°C (°F)	

THE ABOVE DATA IS TO BE USED SOLELY AS AN APPROXIMATE GUIDELINE AND IS SUBJECT TO CHANGE WITHOUT NOTICE. CHIRAL LLC. ASSUMES NO LIABILITY FOR THE ACCURACY, COMPLETENESS, OR VALIDITY OF INFORMATION CONTAINED HEREIN. MATERIAL APPLICATION, PERFORMANCE, AND SUITABILITY MUST BE DETERMINED INDEPENDENTLY BY THE END USER. ALL PRODUCT TRADEMARKS USED ARE PROPERTY OF THEIR RESPECTIVE OWNERS. PLEASE CONTACT YOUR ACCOUNT MANAGER OR CHIRAL TECHNICAL SUPPORT FOR ALL QUESTIONS REGARDING OUR PRODUCTS. ANY TRADEMARKS USED ARE PROPERTY OF THEIR